


# Fast assembly concealed hinge

- ▶ System 8099 mounting plates with eccentric cam height adjustment
- ▶ For Sensys and Intermat

## Face frame mounting plate for screwing on




- ▶ For flat head screws  $\varnothing 4 \times 20$  mm
- ▶ Quality classification under EN 15570, Level 3
- ▶ Hole spacing 40 mm
- ▶ Eccentric cam height adjustment  $\pm 2$  mm
- ▶ Zinc die-cast nickel plated

**BLUE** = Stocked Items

Hole line distance LR mm	Order no. / Distance D mm		PU
	0,0	4,5	
9,5	<b>9 090 882</b>	<b>9 090 884</b>	50 ea.


## Adapter plate for screwing on



- ▶ For 4.5 mm  $\varnothing \times 16$  mm countersunk screws
- ▶ Quality classification under EN 15570, Level 3
- ▶ For connecting parallel adapter
- ▶ Hole line distance 28 and 37 mm
- ▶ Hole spacing 32 mm
- ▶ Oblong hole height adjustment  $\pm 3$  mm
- ▶ Zinc die-cast nickel plated

Distance D mm	Order no.	PU
0,0	<b>9 106 989</b>	50 ea.
1,5	<b>9 106 990</b>	50 ea.
3,0	<b>9 106 991</b>	50 ea.


## Adapter plate with expanding sockets and special screws



- ▶ For  $\varnothing 10 \times 12$  mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ For connecting parallel adapter
- ▶ Hole line distance 28 and 37 mm
- ▶ Hole spacing 32 mm
- ▶ Oblong hole height adjustment  $\pm 2$  mm
- ▶ Zinc die-cast nickel plated

Distance D mm	Order no.	PU
0,0	<b>9 106 983</b>	50 ea.
1,5	<b>9 106 984</b>	50 ea.
3,0	<b>9 106 985</b>	50 ea.

## Adapter plate with premounted Euro screws



- ▶ For  $\varnothing 5 \times 12$  mm drillings
- ▶ Quality classification under EN 15570, Level 3
- ▶ For connecting parallel adapter
- ▶ Hole line distance 28 and 37 mm
- ▶ Hole spacing 32 mm
- ▶ Oblong hole height adjustment  $\pm 3$  mm
- ▶ Zinc die-cast nickel plated

Distance D mm	Order no.	PU
0,0	<b>9 106 986</b>	50 ea.
1,5	<b>9 106 987</b>	50 ea.
3,0	<b>9 106 988</b>	50 ea.